

## PB65 Series 10 LED Rectangular Bar Graph Array Bi-Color

### Features

- \*Popular Industry Standard 10 LED Bar Graph Array
- \*Gray Face, White Segments
- \*Uniform Light Output
- \*IC Compatible
- \*RoHS Compliant




### Absolute Maximum Ratings at T<sub>A</sub> = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<100µA).....	5.0V
Max Forward Current .....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range... ..	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temp.....	260°C for 5 seconds

### Electrical & Optical Characteristics at T<sub>A</sub> = 25°C

Part Number	Emitting Color	Chip Material	Dominant Wave Length	Peak Wave Length	Forward Voltage @20mA (V)		Luminous Intensity @10mA (mcd)	
					Typ	Max	Min	Typ
PB65-BGA10RG1213	Hi-Eff Red Green	GaAsP GaP	626 572	635 567	2.1	2.6	3.7 2.5	8.0 6.0

Package Dimension are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.



Pin Functions	
Pin #	
1 Anode A	11 Cathode J
2 Anode B	12 Cathode I
3 Anode C	13 Cathode H
4 Anode D	14 Cathode G
5 Anode E	15 Cathode F
6 Anode F	16 Cathode E
7 Anode G	17 Cathode D
8 Anode H	18 Cathode C
9 Anode I	19 Cathode B
10 Anode J	20 Cathode A