

# PRODUCT SPECIFICATION

*Part Number*  
**PDM88230x-B01**


## Details

- 2.30 inch (58.34mm) Dot Matrix Display
- 8x8 Array
- Available in Common Anode or Cathode
- Emitting Color: Blue

## Features

- Low power consumption
- RoHS Compliant
- Gray or Black Face, White Segment
- Easy mounting on PCB or socket

## Mechanical Dimensions



### Notes:

1. Dimensions in millimeters [inch], and tolerance is  $\pm 0.25$  [.010] and angle is  $\pm 1^\circ$  unless otherwise noted.
2. Bending  $\leq$  Length\*1%
3. All pins are  $\square 0.50$  [.020]  $\pm$  0.1 [.004]





### Device Selection Guide

Model Number	Chip		Description
	Material	Emitting Color	
PDM88230C-B01	InGaN	Blue	Common Column Cathode
PDM88230A-B01			Common Column Anode

### Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Rating	Unit
Power Dissipation per Dice	PAD	114	mW
Derating Liner from 25°C per Dice	--	0.4	mA/°C
Continuous Forward Current Per Dice	IAF	30	mA
Peak Current Per Dice (duty cycle 1/10, 1KHz)	IPF	100	mA
Reverse Voltage Per Dice	VR	5	V
Electrostatic Discharge (HBM)	ESD	1000	V
Operating Temperature	Topr	°C	
Storage Temperature	Tstg	°C	

### Typical Electrical and Optical Characteristics at Ta=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Voltage Per Segment	VF	--	3.2	3.8	V	IF=20mA
Luminous Intensity Per Segment	Iv	--	60	--	mcd	IF=10mA
Peak Emission Wavelength / Dominant Wavelength	$\lambda P/\lambda d$	--	*465	--	nm	IF=20mA
Reverse Current	IR	--	--	50	$\mu A$	VR=5V
Luminous Intensity Matching Ratio	Iv-m	--	--	2:1	--	IF=10mA

### Typical Electrical/Optical Characteristic Curves

(Ta = 25°C Unless Otherwise Noted)




Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig 5. Relative Intensity vs. Wavelength




Fig 6. Forward Current vs. Ambient Temperature

**Luminous General lv Bin Grade (IF = 10mA)**

A	B	C	D	E	F	G	H	J	K	L	M
0.627	0.816	1.062	1.382	1.797	2.337	3.039	3.952	5.138	6.681	8.686	11.293
0.815	1.061	1.381	1.796	2.336	3.038	3.951	5.137	6.680	8.685	11.292	14.681
N	P	Q	R	S	T	U	V	W	X	Y	1
14.682	19.088	24.815	32.261	41.940	54.523	70.881	92.146	119.791	155.730	202.450	263.185
19.087	24.814	32.260	41.939	54.522	70.880	92.145	119.790	155.729	202.449	263.184	342.141
2	3	4	5	6	7	8	9				
342.142	444.786	578.222	751.690	977.198	1270.359	1651.467	2146.908				
444.785	578.221	751.689	977.197	1270.358	1651.466	2146.907	2790.981				

Remark: Unit=mcd


**Color Rank Limits (IF=20mA)**

2	3	4	5	6
456.0	459.0	462.0	465.0	468.0
459.0	462.0	465.0	468.0	471.0



Remark: Unit=nm

\*Tolerance: ±1

**All Light-On Segments Feature & Pad Position**



**Internal Circuit Diagram**




### *Precautions for Use*

#### 1. Recommended soldering conditions

##### 1.1. Wave soldering


Basic SPEC is  $\leq 5$ sec. When  $260^{\circ}\text{C}$ . If temperature is higher, time should be shorter ( $+10^{\circ}\text{C} \rightarrow -1$ sec.).





##### 1.2. Soldering Iron:

Power dissipation of iron should be smaller than 15W and temp should be controllable. Soldering temperature should be under  $260^{\circ}\text{C}$ , time  $\leq 3$ sec.


***Packing Dimensions***



1 Tray From Box = 8 PCS  
Tray Size:  
L300 x W190 x H20mm



11 Trays Per Inner Box  
Q'TY: 88 PCS.  
Box Size:  
L300 x W205 x H240mm



2 Inner Boxes Per Carton,  
Total Q'TY: 176 Pcs  
Carton Size:  
L431 x W320 x H252mm

Note: 1. Specifications subject to change without notice