

P-tec Corp. Tel:(866) 695 4162  
 2405 Commerce Circle Tel:(719) 589 3122  
 Alamosa CO 81101 Fax:(719) 589 3592  
 www.p-tec.net



## PL03 Series 3mm (T1) LED

### Features

- \*Popular 3mm Lens Style with Flange
- \*1 InGaN Ultra Bright White Chip used
- \*High Light Output
- \*Long Life & Reliability
- \*Integrated Zener Diode for ESD Protection
- \*RoHS Compliant

### Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation .....	120mW
Reverse Voltage (<math><5.0\mu\text{A}</math>).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	$-25^\circ\text{C}$ to $+85^\circ\text{C}$
Storage Temperature Range.....	$-40^\circ\text{C}$ to $+100^\circ\text{C}$
Soldering Temperature (1.6mm below body).....	$260^\circ\text{C}$ for 5 seconds
Electric Static Discharge Threshold (HBM).....	6000V

### Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Chromaticity Coordinates		Viewing Angle $2\theta \frac{1}{2}$ Deg	Reverse Current $V_r=5\text{V}$ ( $\mu\text{A}$ ) Max	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
			X Axis	Y Axis			Typ	Max	Min	Typ
PL03F-WCW24Z	White	InGaN	0.31	0.30	$30^\circ$	50	3.2	4.0	1950	5500

All dimensions are in **Millimeters**. Tolerance is  $\pm 0.25\text{mm}$  unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

