

P-tec Corp. Tel:(866) 695 4162  
 2405 Commerce Circle Tel:(719) 589 3122  
 Alamosa CO 81101 Fax:(719) 589 3592  
 www.p-tec.net



## PL22 Series 8mm Green LED

### Features

- \*Popular 8mm Lens with Flange
- \*Low Current Requirements
- \*High Light Output
- \*RoHS Compliant

### Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation .....	78mW
Reverse Voltage (<math><100\mu\text{A}</math>).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	$-25^\circ\text{C}$ to $+85^\circ\text{C}$
Storage Temperature Range.....	$-40^\circ\text{C}$ to $+100^\circ\text{C}$
Soldering Temperature (1.6mm below body).....	$260^\circ\text{C}$ for 5 seconds

### Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Dominant Wave Length	Peak Wave Length	View Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL22-CDG13	Green	GaP	572	567	$35^\circ$	2.1	2.6	62.0	120.0

All dimensions are in **Millimeters**. Tolerance is  $\pm 0.25\text{mm}$  unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

