



PL84 Series Bi-Color 3 Leaded 5mm (T1^{3/4}) LED

Features

- *Popular 5mm Lens Style with Flange
- *Green & Yellow Chips used
- *Common Cathode
- *White Diffused Lens for a Wide Viewing Angle
- *2.54 mm Lead Spacing
- *Both LED Chips lit will create a 3rd Color
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation (Green).....	78mW
Power Dissipation (Yellow).....	78mW
Reverse Voltage (<100μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
White Diffused Lens			nm	nm	Deg				
PL84-WDGY1301	Green Yellow	GaP GaAsP	567	572	70°	2.1	2.6	13.5	34.0
			585	590		2.1	2.6	10.5	30.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified. An epoxy meniscus may extend about 1mm down the leads.

