

P-tec Corp. Tel:(866) 695 4162
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa, CO 81101 Fax:(719) 589 3592
 www.p-tec.net



PL505 Series 5mm Quad-Level CBI LED

Features

- *4 Wide Circuit Board Indicator LED, Right Angled
- *Housing Material Black Nylon UL94V-2
- *4 Blue LEDs with Color Diffused Lens
- *Rugged and Durable
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation	120mW
Reverse Voltage (<100 μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-40°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL505-4B20	Blue	InGaN/Sapphire	--	465	60°	3.2	1.0	200.0	500.0

All dimensions are in **Millimeters**. Tolerance is ± 0.5mm unless otherwise specified.

