

P-tec Corp. Tel:(866) 695 4162
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa, CO 81101 Fax:(719) 589 3592
 www.p-tec.net



PL505 Series 5mm Quad-Level CBI LED

Features

- *4 Wide Circuit Board Indicator LED, Right Angled
- *Housing Material Black Nylon UL94V-2
- *4 Green LEDs with Color Diffused Lens
- *Rugged and Durable
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation	78mW
Reverse Voltage (<math><100 \mu\text{A}</math>).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-40°C to $+85^\circ\text{C}$
Storage Temperature Range.....	-40°C to $+100^\circ\text{C}$
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
PL505-4G13	Green	GaP	567	572	38°	2.1	2.6	11.0	25.0

All dimensions are in **Millimeters**. Tolerance is $\pm 0.5\text{mm}$ unless otherwise specified.

