



PL102 Series 1.8mm Miniature Bi-Level LED Holder

Features

- *Miniature Bi-Level LED Holder, Right Angled
- *Space saving Circuit Board Indicator
- *High Light Output
- *Housing Material Black Nylon UL94V-2
- *2 Bright Red LEDs with Color Diffused Lens used
- *Color Arranged from Top to Bottom
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	90mW
Reverse Voltage (<100 μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range	-25°C to + 85°C
Storage Temperature Range	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL102-2R24	Red	GaP	700	650	30°	2.1	3.0	4.0	8.0

All dimensions are in **Millimeters**. Tolerance is ± 0.5mm unless otherwise specified.

