



PL309 Series 3mm LED Right Angle Bi-Level Holder

Features

- *Space Saving Bi-Level PCB Indicator
- *Housing Material Black Nylon UL94V-2
- *High Light Output
- *2 Super Bright Red Leds with Color Diffused Lens used
- *Leds are arranged from Top to Bottom
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation.....	66mW
Reverse Voltage (<100 μA).....	4.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
PL309-2R21	Deep Red	AlGaAs	660	643	55°	1.8	2.2	60.0	100.0

All dimensions are in **Millimeters**. Tolerance is $\pm 0.5\text{mm}$ unless otherwise specified.

