



PL315 Series Bi-Color 3mm LED Right Angle Bi-Level Holder

Features

- *Space Saving Bi-Level PCB Indicator
- *Housing Material Black Nylon UL94V-0
- *High Light Output
- *2 Bi-Color Three Leaded Yellow/Green LEDs used
- *LEDs arranged from Top to Bottom
- *Common Cathode
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	78mW
Reverse Voltage (<100 μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260° for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Lumious Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
			nm	nm	Deg				
PL315-2YG0113	Yellow Green	GaAsP GaP	585 567	590 572	80°	2.1 2.1	2.6 2.6	10.0 11.0	20.0 20.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

