

P-tec Corp. Tel:(866) 695 4162
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa CO 81101 Fax:(719) 589 3592
 www.p-tec.net



PL506 Series 5mm LED Bi-Color Right Angle Holder

Features

- *Popular right angle PCB indicator
- *Housing material black nylon UL94V-2
- *High light output
- *1 Bright red LED and 1 yellow green with white diffused lens used
- *Reliable and rugged
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation.....	72mW
Reverse Voltage (<100 μ A).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)
						Typ	Max	Typ
White Diffused Lens			nm	nm	Deg	Typ	Max	Typ
PL506-1RG1213	Red/Yellow Green	GaAsP/GaP	635/567	626/572	95°	2.1/2.1	2.6/2.6	15.0/13.0

All dimensions are in **Millimeters**. Tolerance is $\pm 0.25\text{mm}$ unless otherwise specified.

