

PL519 Series 5mm LED Snap-in Panel Mount Holder

Features

- *Snap-in Design Requires no Hardware
- *Mounting Hole 6.35 mm (0.25")
- *Housing Material Black Nylon UL94V-2
- *1 Super Bright Red LED with Color Diffused Lens used
- *Standard Terminals
- *RoHS Compliant

Absolute Maximum Ratings at T_A = 25°C

Power Dissipation.....	66mW
Reverse Voltage (<100μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

Electrical & Optical Characteristics at T_A = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
			nm	nm	Deg	Typ	Max	Min	Typ
PL519-1R21	Deep Red	AlGaAs	660	643	38°	1.8	2.2	90.0	160.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

