

## PL520 Series 5mm LED Snap-in Panel Mount Holder

### Features

- \*Snap-in Design Requires no Hardware
- \*Mounting Hole 6.35 mm (0.25")
- \*Housing Material Black Nylon UL94V-2
- \*1 Super Bright Red LED with Color Diffused Lens used
- \*26AWG 6" (+) Red and (-) Black Wire Leads
- \*RoHS Compliant

### Absolute Maximum Ratings at T<sub>A</sub> = 25°C

Power Dissipation.....	66mW
Reverse Voltage (<100µA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-40°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

### Electrical & Optical Characteristics at T<sub>A</sub> = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
6" Wire Leads			nm	nm	Deg				
PL520-1R21-2	Deep Red	AlGaAs	660	643	30°	1.8	2.2	110.0	200.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

